ISSN NO. 2456-3129

IJEPAS

International Journal of Engineering, Pure and Applied Sciences,
Vol. 11, No.1, March 2026

DEVELOPMENT OF AN INTELLIGENT BIODIESEL FUEL MANAGEMENT STRATEGY FOR ENHANCED ENERGY EFFICIENCY AND REDUCED EXHAUST EMISSIONS

Pankaj[1] & Rupinder Singh Johal[2]
Research Scholar, Department of Mechanical Engg., Arni University, Indora , H.P.
Professor, Department of Mechanical Engg., Arni University, Indora , H.P.

ABSTRACT
The increasing demand for energy, depletion of conventional petroleum resources and growing environmental concerns have intensified the need for sustainable alternative fuels in the transportation and industrial sectors. Biodiesel has emerged as a promising renewable substitute for conventional diesel because of its biodegradability, lower sulphur content, renewable origin and potential to reduce several harmful exhaust emissions. However, variations in biodiesel composition, fuel properties, engine operating conditions and combustion characteristics create challenges in achieving consistent energy efficiency and emission performance. The present research proposes the development of an intelligent biodiesel fuel management strategy that integrates fuel property assessment, adaptive engine control, real-time sensor monitoring and computational optimisation to improve engine performance while minimising exhaust emissions. The proposed framework incorporates intelligent algorithms to regulate fuel injection timing, injection pressure, fuel quantity and air–fuel interaction according to engine load, speed and biodiesel blend characteristics. Artificial intelligence and machine learning techniques can further support predictive assessment of fuel consumption, combustion efficiency and emission behaviour. The framework considers important performance indicators, including brake thermal efficiency, brake-specific fuel consumption, nitrogen oxides, carbon monoxide, unburnt hydrocarbons and particulate matter. A multi-objective optimisation approach is proposed to balance energy efficiency, emission reduction and operational reliability. The research establishes a conceptual and methodological foundation for intelligent biodiesel utilisation in diesel engines. It also identifies the potential contribution of smart fuel management systems towards cleaner transportation, renewable energy integration and sustainable industrial development.

Keywords: Biodiesel; Intelligent Fuel Management; Artificial Intelligence; Energy Efficiency; Exhaust Emissions; Machine Learning; Diesel Engine; Adaptive Control; Sustainable Energy.

INTRODUCTION

The global energy sector is undergoing a significant transition towards renewable and environmentally sustainable energy sources. Conventional fossil fuels continue to dominate transportation, agriculture, electricity generation and industrial operations. However, their extensive consumption has contributed to greenhouse gas emissions, atmospheric pollution, climate change and increasing concerns regarding long-term energy security. Diesel engines, in particular, are widely employed in heavy-duty vehicles, agricultural machinery, construction equipment, generators and industrial applications because of their durability, high torque characteristics and operational efficiency. Despite these advantages, conventional diesel combustion produces pollutants such as nitrogen oxides (NOx), carbon monoxide (CO), unburnt hydrocarbons (HC) and particulate matter (PM).

Biodiesel has attracted considerable research attention as an alternative fuel capable of reducing dependence on petroleum-derived diesel. It is generally produced through the transesterification of vegetable oils, animal fats or waste cooking oils using an alcohol and a suitable catalyst. The resulting fatty acid alkyl esters possess fuel characteristics that permit their utilisation in compression-ignition engines, either in pure form or blended with conventional diesel.

One of the major advantages of biodiesel is its renewable origin. Its relatively high oxygen content can promote more complete combustion, potentially reducing carbon monoxide, unburnt hydrocarbons and particulate emissions under suitable operating conditions. Furthermore, biodiesel generally exhibits very low sulphur content compared with conventional petroleum diesel. These characteristics make it an attractive component of sustainable fuel strategies.

Nevertheless, biodiesel presents certain operational challenges. Its higher viscosity, density and surface tension, together with comparatively lower calorific value, can influence fuel atomisation, injection characteristics, combustion duration and engine performance. Depending on the feedstock, blend ratio and engine operating conditions, biodiesel may also increase nitrogen oxide emissions. Consequently, replacing conventional diesel with biodiesel without modifying or optimising engine management

parameters may not produce the expected improvements in overall performance.

The increasing availability of intelligent monitoring technologies provides an opportunity to address these limitations. Modern diesel engines incorporate electronic control units, pressure sensors, temperature sensors, exhaust gas monitoring systems and electronically controlled fuel injection mechanisms. These technologies generate operational information that can be processed through computational intelligence techniques to improve fuel utilisation.

An intelligent biodiesel fuel management strategy can therefore be developed by integrating fuel quality information, engine operating parameters, sensor-based monitoring and adaptive optimisation algorithms. Such a system can determine appropriate fuel injection parameters according to the characteristics of the biodiesel blend and the prevailing engine operating conditions.

The present research focuses on developing a comprehensive conceptual framework that combines intelligent fuel management, adaptive combustion control and multi-objective optimisation to enhance energy efficiency and reduce exhaust emissions. The proposed approach is particularly relevant to diesel engines operating under variable loads and using biodiesel blends of different compositions.

REVIEW OF LITERATURE

Biodiesel as an Alternative Renewable Fuel

Biodiesel is commonly recognised as a renewable alternative to petroleum diesel. Its production from biological feedstocks provides opportunities for agricultural resource utilisation, waste management and diversification of energy supply. Research by Ma and Hanna (1999) established the importance of transesterification as a principal process for producing biodiesel with properties suitable for diesel engine applications.

Demirbas (2009) discussed the potential of biodiesel as an alternative energy source and highlighted its environmental and energy-security implications. The study emphasised that the sustainability of biodiesel depends not only on combustion performance but also on feedstock availability, production processes and lifecycle environmental impacts.

The use of waste cooking oil and non-edible oil resources has received particular attention because these feedstocks may reduce competition with food production. However, variations in fatty acid composition and processing quality can affect important fuel properties, including viscosity, oxidation stability and calorific value.

Biodiesel and Diesel Engine Performance

Engine performance is influenced by fuel viscosity, density, heating value, cetane number and oxygen content. Biodiesel generally has a lower calorific value than petroleum diesel, which can result in increased fuel consumption when the same amount of useful energy is required.

Agarwal (2007) examined the utilisation of biodiesel in diesel engines and discussed its potential as an alternative fuel. The findings of earlier research indicate that biodiesel can be used in conventional compression-ignition engines, although performance outcomes depend on the fuel composition, engine design and operating conditions.

Lapuerta et al. (2008) reviewed the effect of biodiesel fuels on diesel engine emissions and identified significant variations across different pollutants. Their discussion demonstrates that biodiesel does not produce uniform emission reductions under all operating conditions.

Biodiesel and Exhaust Emission Characteristics

The oxygenated nature of biodiesel can improve combustion characteristics and contribute to reductions in carbon monoxide, hydrocarbons and particulate matter. However, nitrogen oxide emissions may increase in certain engine configurations because of changes in combustion temperature, injection behaviour and oxygen availability.

Knothe (2010) examined the historical development and technological characteristics of biodiesel, including its fuel properties and application challenges. This research highlights the importance of considering the chemical composition of biodiesel when evaluating its performance.

The emission behaviour of biodiesel is also affected by engine load, injection pressure, injection timing and combustion chamber characteristics. Therefore, the selection of an appropriate biodiesel blend should be accompanied by suitable engine calibration.

Intelligent Control and Artificial Intelligence in Engine Management

The application of artificial intelligence in automotive engineering has expanded the possibilities of predictive maintenance, fuel consumption estimation, combustion control and emission optimisation. Machine learning models can identify complex relationships between fuel properties, engine operating conditions and performance indicators.

Artificial neural networks, adaptive neuro-fuzzy inference systems, genetic algorithms and other computational intelligence methods can be employed to develop predictive and optimisation models. These approaches are particularly useful when the relationships between input parameters and engine responses are nonlinear.

Despite the development of intelligent engine control technologies, the integration of fuel quality

assessment, biodiesel blend identification and adaptive fuel injection management within a unified optimisation framework remains an important area for further investigation.

RESEARCH METHODOLOGY

Research Design

The present study adopts a quantitative, computational and engineering-oriented research design. It proposes the development of an intelligent fuel management framework through the integration of fuel characterisation, engine performance monitoring, predictive modelling and optimisation.

The proposed methodology consists of five interconnected stages: biodiesel preparation and characterisation; engine performance and emission data acquisition; development of predictive machine learning models; intelligent optimisation of engine operating parameters; and performance evaluation and comparative assessment.

The framework is intended for experimental validation using a single-cylinder or multi-cylinder compression-ignition diesel engine equipped with an electronically controlled fuel injection system.

Biodiesel Preparation and Fuel Characterisation

Biodiesel can be prepared through the transesterification of vegetable oils, non-edible oils or waste cooking oils. The process involves reacting triglycerides with an alcohol, generally methanol, in the presence of an alkaline or acidic catalyst. The reaction produces fatty acid methyl esters (FAME) and glycerol as a by-product.

For the proposed investigation, different biodiesel blends may be considered to evaluate their suitability under varying engine operating conditions.

The fuel samples should be characterised according to recognised ASTM or EN testing procedures. The principal fuel properties include density, kinematic viscosity, calorific value, cetane number, flash point and oxidation stability. These properties provide essential input variables for the intelligent fuel management system. Fuel characterisation also helps identify differences between biodiesel batches that may influence combustion and engine performance.

Experimental Engine Parameters

The proposed intelligent management strategy considers important engine operating parameters that influence energy conversion and exhaust emissions.

The engine should be equipped with suitable measurement instruments, including a dynamometer, fuel consumption meter, thermocouples, pressure sensors and exhaust gas analysers. Data acquisition should be conducted under controlled conditions to ensure consistency between different biodiesel blends. Measurements should be recorded at different engine speeds and loads to capture the influence of operating conditions on fuel consumption, combustion performance and exhaust emissions.

Development of the Intelligent Fuel Management Framework

Module 1: Fuel Quality Monitoring. This module evaluates the physical and chemical properties of the biodiesel blend. Information regarding viscosity, density, heating value and blend composition is supplied to the control system. The fuel quality information helps determine the initial injection requirements.

Module 2: Real-Time Engine Monitoring. The monitoring module collects operational data through sensors installed in the engine. Parameters such as engine speed, load, temperature, fuel consumption and exhaust emissions are continuously monitored.

Module 3: Artificial Intelligence-Based Prediction. Machine learning algorithms analyse the relationship between fuel characteristics, engine operating conditions and performance indicators. The predictive model estimates fuel consumption, thermal efficiency and exhaust emissions for different combinations of operating parameters.

Module 4: Adaptive Fuel Control. The optimisation module uses predictive information to determine suitable fuel injection timing, injection pressure and fuel delivery quantity. The electronic control unit receives the optimised control signals and adjusts engine operation within manufacturer-defined safety limits.

Artificial Intelligence and Machine Learning Techniques

Artificial Neural Network (ANN): An ANN can be employed to estimate engine performance and emission characteristics using multiple input variables. The input layer receives fuel properties and engine operating parameters, while the output layer predicts BTE, BSFC, NOx, CO, HC and particulate emissions.

Random Forest Regression: Random Forest can be used to identify the relative importance of fuel properties and engine operating variables. It is particularly useful for modelling nonlinear relationships and reducing the influence of individual noisy observations.

Adaptive Neuro-Fuzzy Inference System (ANFIS): ANFIS combines fuzzy logic with neural network learning. It can represent complex relationships between engine load, biodiesel composition, injection pressure and combustion characteristics.

Genetic Algorithm (GA): Genetic algorithms can be applied to identify suitable combinations of engine

IJEPAS
International Journal of Engineering, Pure and Applied Sciences,
Vol. 11, No.1, March 2026

control parameters. The optimisation process evaluates alternative solutions through selection, crossover and mutation operations.
A hybrid ANN–GA or ANFIS–GA approach can be investigated to combine predictive modelling with parameter optimisation. The selection of the final model should depend on prediction accuracy, computational requirements, robustness and real-time implementation capability.

Mathematical Formulation of Engine Performance

The intelligent fuel management strategy requires mathematical evaluation of engine performance.

A. Brake Power

$$BP = (2\pi NT) / 60{,}000$$

BP = brake power (kW); N = engine speed (rpm); T = brake torque (Nm).

B. Brake Thermal Efficiency

$$BTE = [BP \times 3600 / (\dot{m}f \times CV)] \times 100$$

$\dot{m}f$ = fuel mass flow rate (kg/h); CV = calorific value (kJ/kg).

C. Brake-Specific Fuel Consumption

$$BSFC = \dot{m}f / BP$$

A lower BSFC generally indicates improved fuel economy, although comparisons between fuels should also account for differences in calorific value.

D. Air–Fuel Ratio

$$AFR = \dot{m}a / \dot{m}f$$

$\dot{m}a$ represents the mass flow rate of intake air.
These mathematical relationships provide a quantitative basis for comparing the performance of conventional diesel and different biodiesel blends.

Multi-Objective Optimisation Model

The proposed fuel management strategy aims to improve thermal efficiency while reducing fuel consumption and exhaust emissions. These objectives may conflict with one another. For example, changing injection timing to reduce NOx may affect fuel consumption or combustion efficiency.
A multi-objective optimisation model is therefore proposed:

Maximise: BTE

Minimise: (BSFC, NOx, CO, HC, PM)

The optimisation problem can be represented using a weighted objective function:

$$J = w_1(BSFC/BSFC_0) + w_2(NOx/NOx_0) + w_3(CO/CO_0) + w_4(HC/HC_0) + w_5(PM/PM_0) - w_6(BTE/BTE_0)$$

J represents the combined optimisation objective; w_1 to w_6 represent assigned weights; and subscript 0 represents the reference diesel operating condition.
The weights should be selected according to application-specific priorities and regulatory requirements. Normalisation is necessary because the indicators have different units and numerical scales.
The optimisation variables include biodiesel blend ratio, fuel injection pressure, fuel injection timing, fuel injection quantity, and engine speed and load operating conditions. The optimisation must also satisfy physical and operational constraints, including maximum cylinder pressure, exhaust temperature, injection system limitations and applicable emission standards.
A Pareto-based optimisation method may be particularly suitable because it identifies multiple non-dominated solutions rather than forcing all performance objectives into a single preferred outcome.

RESULTS AND DISCUSSION

Expected Influence of Biodiesel Blends on Engine Performance

Biodiesel blends can influence engine performance through variations in energy content, viscosity and combustion characteristics. Low and moderate biodiesel blends generally require less extensive engine modification than pure biodiesel. However, their performance must be evaluated under controlled experimental conditions.
A lower heating value may increase the fuel quantity required to produce equivalent brake power. At the same time, the oxygen content of biodiesel can support combustion and influence carbon monoxide and hydrocarbon formation.
The proposed intelligent management system addresses these variations by adapting injection parameters according to the measured fuel properties and engine operating conditions.

Comparative Evaluation of Energy Efficiency

The principal objective of the proposed framework is to improve the utilisation of fuel energy. Conventional fixed calibration may not provide optimal injection characteristics across different biodiesel blends and engine loads.
An intelligent controller can potentially improve the relationship between fuel delivery, air availability and combustion duration. The resulting changes may contribute to better brake thermal efficiency and reduced specific fuel consumption.
However, improvements should not be assumed for every blend or operating condition. The actual performance will depend on engine configuration, injection system design, fuel quality and calibration accuracy.

Expected Effects on Exhaust Emissions

- Carbon monoxide: The additional oxygen in biodiesel can support more complete oxidation of carbon-containing compounds.

IJEPAS
International Journal of Engineering, Pure and Applied Sciences,
Vol. 11, No.1, March 2026

- Unburnt hydrocarbons: Improved combustion may reduce incomplete combustion products.
- Particulate matter: Biodiesel can reduce soot formation under suitable conditions because of its oxygenated molecular structure and low aromatic content.
- Nitrogen oxides: NOx behaviour is more complex and may increase or decrease depending on combustion temperature, injection timing, engine load and fuel composition.

The intelligent controller is designed to consider these competing effects when determining appropriate engine operating parameters.

COMPARATIVE PERFORMANCE EVALUATION FRAMEWORK

Proposed Data Analysis and Model Validation

The effectiveness of the intelligent management system should be evaluated through statistical and computational analysis. The experimental dataset should be divided into training, validation and testing subsets to assess the predictive capability of the machine learning models.

Mean Absolute Error (MAE)

$$MAE = (1/n) \Sigma |y_i - \hat{y}_i|$$

A lower MAE indicates a smaller average absolute prediction error.

Root Mean Square Error (RMSE)

$$RMSE = \sqrt{[(1/n) \Sigma (y_i - \hat{y}_i)^2]}$$

A lower RMSE indicates lower prediction error, with greater sensitivity to larger errors.

Coefficient of Determination

$$R^2 = 1 - [\Sigma(y_i - \hat{y}_i)^2 / \Sigma(y_i - \bar{y})^2]$$

An R^2 value closer to unity generally indicates a stronger correspondence between observed and predicted values.

Cross-validation should be applied to reduce the possibility of overfitting. Furthermore, experimental validation under different engine loads and biodiesel compositions is necessary before deploying the proposed controller in practical applications.

ROLE OF INTELLIGENT CONTROL IN IMPROVING ENERGY EFFICIENCY

The integration of intelligent control mechanisms can improve the adaptability of diesel engines operating with biodiesel. Conventional control systems generally employ predetermined calibration maps, which may not fully account for variations in fuel composition and quality.

The proposed system uses sensor-based information to estimate the current operating condition and determine suitable control parameters. For example, when the system detects a change in engine load, the predictive model can evaluate the corresponding fuel delivery requirements. Similarly, variations in biodiesel viscosity and density can be considered when determining appropriate injection conditions.

An adaptive controller may also identify operating regions associated with increased fuel consumption or undesirable emission formation. This information can be used to select alternative injection strategies within safe operating limits.

The effectiveness of such a system depends on sensor accuracy, model generalisation, control response time and the reliability of the electronic fuel injection mechanism.

Environmental and Economic Implications

The proposed strategy has potential environmental benefits through improved fuel utilisation and better control of exhaust emissions. Biodiesel produced from waste cooking oil and other sustainable feedstocks can also contribute to waste valorisation and reduced dependence on fossil-derived resources.

From an economic perspective, intelligent fuel management may reduce unnecessary fuel consumption and support predictive maintenance by identifying abnormal operating conditions. However, the initial installation of sensors, electronic control equipment and computational systems may increase implementation costs.

The economic feasibility of the proposed framework should therefore be assessed by considering fuel savings, maintenance costs, equipment investment, fuel availability and the expected operational life of the engine.

Proposed Implementation Strategy

Stage 1: Fuel preparation and testing. Biodiesel should be produced using an appropriate feedstock and tested for viscosity, density, calorific value, cetane number and oxidation stability.

Stage 2: Experimental data collection. A diesel engine test rig should be used to collect fuel consumption, performance and emission data for selected biodiesel blends under different loads and speeds.

Stage 3: Machine learning model development. ANN, Random Forest and ANFIS models should be trained using experimentally collected datasets. Their performance should be compared using MAE, RMSE and R^2.

Stage 4: Optimisation and controller development. A multi-objective optimisation algorithm should determine appropriate injection timing, pressure and fuel delivery settings. The resulting control strategy should be implemented through an electronic control unit.

Stage 5: Experimental validation. The optimised control system should be evaluated against conventional diesel operation and fixed-calibration biodiesel operation. Repeated experiments should be

IJEPAS
International Journal of Engineering, Pure and Applied Sciences,
Vol. 11, No.1, March 2026

conducted to establish the consistency and statistical significance of the observed differences.

Stage 6: Practical assessment. The final stage should examine operational reliability, fuel economy, emission compliance, maintenance requirements and economic feasibility.

LIMITATIONS AND FUTURE RESEARCH DIRECTIONS

Although intelligent biodiesel fuel management offers considerable technological potential, certain limitations require attention.

First, machine learning models depend on the availability and quality of experimental datasets. Models developed using a particular engine configuration may not perform equally well in engines with different combustion chamber designs or injection systems.

Second, biodiesel composition varies according to feedstock, production methodology and storage conditions. Consequently, the proposed framework requires appropriate fuel characterisation and periodic model recalibration.

Third, NOx emissions may respond differently to changes in injection timing, combustion temperature and biodiesel composition. Therefore, emission reduction should be treated as a multi-objective engineering problem rather than an assumption that every pollutant will decrease simultaneously.

Future investigations should explore digital twin technology, real-time fuel quality estimation, hybrid machine learning algorithms and model predictive control. Integration with Internet of Things (IoT) platforms could also support remote engine monitoring and predictive maintenance.

Further research should examine the application of intelligent biodiesel management in agricultural tractors, commercial transportation, industrial generators and distributed power generation systems. Lifecycle assessment and techno-economic analysis would provide additional evidence regarding the sustainability of the complete biodiesel utilisation system.

CONCLUSION

The development of an intelligent biodiesel fuel management strategy represents a promising approach to improving the performance and environmental characteristics of compression-ignition engines operating with renewable fuels. Biodiesel offers potential advantages in terms of renewable feedstock utilisation, lower sulphur content and reduced emissions of certain pollutants. Nevertheless, variations in viscosity, density, calorific value and combustion characteristics create challenges that require effective engine calibration and fuel management.

The present research proposes an integrated framework combining biodiesel fuel characterisation, real-time engine monitoring, artificial intelligence-based prediction and multi-objective optimisation. The framework is designed to regulate fuel injection timing, injection pressure and fuel delivery according to engine operating conditions and biodiesel properties. Machine learning techniques, including artificial neural networks, Random Forest and adaptive neuro-fuzzy inference systems, can provide predictive support for estimating engine efficiency, fuel consumption and exhaust emissions.

The proposed approach places particular emphasis on balancing brake thermal efficiency, brake-specific fuel consumption and the emission characteristics of NOx, CO, HC and particulate matter. Its multi-objective structure recognises that improvements in one performance indicator may influence other indicators, making coordinated optimisation necessary.

The framework provides a conceptual foundation for developing adaptive and intelligent fuel management systems. Its practical effectiveness, however, must be established through controlled engine experiments, statistical validation and comparison with conventional calibration strategies. Successful implementation could contribute to improved biodiesel utilisation, reduced dependence on petroleum fuels and the advancement of cleaner and more energy-efficient transportation and industrial systems.

REFERENCES

[1]. Agarwal, A. K. (2007). Biofuels (alcohols and biodiesel) applications as fuels for internal combustion engines. Progress in Energy and Combustion Science, 33(3), 233–271. https://doi.org/10.1016/j.pecs.2006.08.003

[2]. Demirbas, A. (2009). Progress and recent trends in biodiesel fuels. Energy Conversion and Management, 50(1), 14–34. https://doi.org/10.1016/j.enconman.2008.09.001

[3]. Knothe, G. (2010). Biodiesel and renewable diesel: A comparison. Progress in Energy and Combustion Science, 36(3), 364–373. https://doi.org/10.1016/j.pecs.2009.11.004

[4]. Lapuerta, M., Armas, O., & Rodríguez-Fernández, J. (2008). Effect of biodiesel fuels on diesel engine emissions. Progress in Energy and Combustion Science, 34(2), 198–223. https://doi.org/10.1016/j.pecs.2007.07.001

[5]. Ma, F., & Hanna, M. A. (1999). Biodiesel production: A review. Bioresource Technology, 70(1), 1–15. https://doi.org/10.1016/S0960-8524(99)00025-5

[6]. Murugesan, A., Umarani, C., Chinnusamy, T. R., Krishnan, M., Subramanian, R., & Neduzchezhain, N. (2009). Production and analysis of bio-diesel from non-edible oils—A review. Renewable and Sustainable Energy

IJEPAS

International Journal of Engineering, Pure and Applied Sciences,
Vol. 11, No.1, March 2026

Reviews, 13(4), 825–834. https://doi.org/10.1016/j.rser.2008.02.003

[7]. Xue, J., Grift, T. E., & Hansen, A. C. (2011). Effect of biodiesel on engine performances and emissions. Renewable and Sustainable Energy Reviews, 15(2), 1098–1116. https://doi.org/10.1016/j.rser.2010.11.016

[8]. Hoekman, S. K., Broch, A., Robbins, C., Ceniceros, E., & Natarajan, M. (2012). Review of biodiesel composition, properties, and specifications. Renewable and Sustainable Energy Reviews, 16(1), 143–169. https://doi.org/10.1016/j.rser.2011.07.143

[9]. Atabani, A. E., Silitonga, A. S., Badruddin, I. A., Mahlia, T. M. I., Masjuki, H. H., & Mekhilef, S. (2012). A comprehensive review on biodiesel as an alternative energy resource and its characteristics. Renewable and Sustainable Energy Reviews, 16(4), 2070–2093. https://doi.org/10.1016/j.rser.2012.01.003

[10]. Heywood, J. B. (1988). Internal combustion engine fundamentals. McGraw-Hill.